

Gas Detection for Use with Aspirated Smoke Detection

Xtralis the manufacturer of the market leading VESDA aspirating smoke detection (ASD) technology has developed the industries first multi-hole aspirated gas detector.

When used with the VESDA range of ASD products; VESDA ECO provides the industries 1st combine aspirated smoke and gas detection system.

VESDA ECO provides early warning of toxic, oxygen and flammable gas hazards to protect personnel and property whilst ensuring business continuity.

Applications include:

- Battery charging rooms
- Boiler plant rooms
- Commercial kitchens
- Parking garages
- Utility / service tunnels
- Refrigerated stores and plant rooms
- Water treatment and sewerage plants
- Power generation plants
- Metal processing plants
- and more...

How It Works

VESDA ECO uses an existing or new VESDA aspirating pipe network to actively monitor for gas escapes and build-ups.

Each ECO gas detector can house up to two gas sensors, and additional detectors can be added easily to the VESDA pipe network to monitor more gases if required. Pre-calibrated sensor cartridges are easily replaced in the field and make converting to different gas sensors or replacing sensors a simple task.

The VESDA ECO detector is configured using Xtralis VSC configuration software and can be remotely monitored using Xtralis VSM4 monitoring software. Both VSC and VSM can be used to download data from the on-board memory card for data analysis and trending of historical data.

Integration with other building systems, including fire alarm control panels, PLCs, HVAC and building management systems, provides real-time situational awareness for intelligent emergency response.

VESDA ECO by Xtralis provides significant installation and routine maintenance cost savings over conventional multi-point gas detection solutions, by reducing the number of detectors required to cover an area and by providing easy access for routine maintenance.

Hazardous area certified variants of VESDA ECO are available (Approval pending).



Features

- Toxic, Oxygen or Flammable gas detection
- Single or dual gas versions
- Factory calibrated sensor cartridges
- Integral alarm status LEDs
- Integrates with PLCs/HVAC/BMS/FACP
- Configurable relays
- 4-20 mA analog outputs
- RS485 Modbus output
- On-board event logging
- On-board fault diagnostics
- Integral gas test port
- Remote reset

Approvals

CE

Electrical safety:

Conforms to ANSI/UL Std 61010-1
Certified to CAN/CSA Std C22.2 No. 61010-1
EN 61010-1

EMC:

FCC 47CFR Part 15B class B
ICES 003
EN 50270

Others:

LCPB, VdS, AFNOR compatible for use with Xtralis EN54-20 approved ASD

LOM approved to UNE 23300 (CO & CO+NO₂)

AQISQ – CMC Pattern Approval

CCCF – CFE, GB:15322.1

VNIPO

Hazardous area, ATEX, ANSI/ISA, CSA (pending)

1) Consult with Xtralis if application requires removal of interferent gases.

VESDA ECO™ Detector

Gas Detection and Environmental Monitoring

VESDA ECO Ordering information

VESDA ECO gas detectors come complete with the main housing, sensor cartridge, data storage card and USB interface cable. Two variants are available based on detector outputs:

Part number structure: ECO-D-X-AA-BB

Select output option, replace X with either:

B Relays, and analogue & serial outputs

R Relay and analogue outputs only (Not approved for US markets)

Single Gas Units

Replace AA with the relevant gas type number below and remove BB:

- 11 Hydrogen (H₂) 0-100% LFL
- 12 Methane (CH₄) 0-100% LFL
- 13 Propane (C₃H₈) 0-100% LFL
- 14 Hydrogen (H₂) 0-2000 ppm
- 15 Gasoline Vapour 0-100% LFL
- 16 Pentane (C₅H₁₂) 0-100% LFL
- 19 Ammonia (NH₃) 0-100% LFL
- 20 Alcohols 0-100% LFL
- 31 Oxygen depletion only (O₂) 0-25% v/v
- 32 Oxygen depletion and enrichment (O₂) 0-25% v/v
- 41 Carbon Monoxide (CO) 0-500 ppm
- 42 Ammonia (NH₃) 0-100 ppm
- 43 Hydrogen Sulphide (H₂S) 0-100 ppm
- 44 Sulphur Dioxide (SO₂) 0-10 ppm
- 45 Nitrogen Dioxide (NO₂) 0-10 ppm
- 47 Chlorine (Cl₂) 0-20 ppm
- 49 Carbon Dioxide (CO₂) 0-5% v/v

Dual Gas Units

Select one of the available combinations below. Replacing AA and BB with the preferred combination. Other combinations are available upon request:

- 11 – 31 Hydrogen and Oxygen
- 12 – 31 Methane and Oxygen
- 12 – 41 Methane and Carbon Monoxide
- 12 – 43 Methane and Hydrogen Sulphide
- 13 – 31 Propane and Oxygen
- 31 – 41 Oxygen and Carbon Monoxide
- 41 – 43 Carbon Monoxide and Hydrogen Sulphide
- 41 – 45 Carbon Monoxide and Nitrogen Dioxide

Example: ECO-D-B-12-41

An ECO detector with relay, analogue and serial outputs for Methane and Carbon Monoxide.

Replacement sensor cartridge part number structure: ECO-SC-AA-BB

Where SC = Sensor Cartridge, AA-BB are 1st and 2nd gas types (see above).

Installation

VESDA ECO is designed to press fit on to VESDA air-sampling pipe work. To fit VESDA ECO simply remove a 60 mm section of pipe when using 25 mm OD air-sampling pipe work or 4" for ¾" BSP pipe.

VESDA ECO provides total flexibility to install one or more detectors anywhere on the pipe network to enable monitoring of a specific point, zone or total area.



Specifications

Supply Voltage
18-30 VDC
Power Consumption @ 24 VDC
3.6 W (max)
Current Consumption
Typically 60 mA @ 24 V DC for a dual gas (flammable / toxic) quiescent. 85 mA when in alarm.
Dimensions (WHD)
34 mm x 125 mm x 110 mm (1.3" x 4.9" x 4.4")
Weight
250 g (0.6 pounds)
IP/NEMA ratings
IP65 and NEMA 4
Operating Conditions
Temperature typically -20°C to 50°C (-4°F to 122°F) gas dependant. O ₂ -20°C to 55°C (-4°F to 131°F) NH ₃ -20°C to 40°C (-4°F to 104°F) Humidity: 10-95% RH, non-condensing
Pipe Size
External Diameter 25 mm (EU), ¾" (US/CAN)
Wire/Terminal size
1.5 mm ² 16 AWG maximum
Cable Access and Termination
2 x PG9 cable glands, to suit 4.0 to 8.5 mm (0.157" to 0.335") outer cable diameter
Accuracy
+/- 5%
Outputs
4 wire RS 485 Modbus RTU (2 wire data comms + 2 wire power) Four (4) programmable relays 30 VDC 1A One (1) 4-20 mA output per sensor
Onboard Memory Card
Micro SD card 2 GB (50,000 events)



FireSense Benelux
Stammerkamp 19
1112 VE DIEMEN
The Netherlands
T +31 (0)20 669 41 90
F +31 (0)20 669 18 52
E info@firesense.nl
I www.firesense.nl

